

1/13

2




FIG. 1





FIG. 2



4/13




FIG. 4

5/13




FIG. 5

6/13




FIG. 6

7/13

400

Select Host and Configuration Policy

Select one of the Hosts To Configure 402

Central Office Server	▼
Accounting Dept. Server	
Shipping Dept. Server	
E-Commerce Sales Server A	

Select one Configuration Policies to Use 404

Bronze Configuration	▼
Silver Configuration	
Gold Configuration	
Platinum Configuration	

406 More Info

408 Next> Cancel

FIG. 7

8/13




FIG. 8

9/13




FIG. 9

10/13




FIG. 10

11/13

128a...n




FIG. 11

2074937-04707

270

770

Configuration Policy Tool

772 Element Configuration Policy	774 Throughput	776 Availability	778 Latency
Switch Element 132	10-100 MB/sec	Standard	High
Switch Element 133	100-200 MB/sec	High	Standard
.
HBA Element 320	10-100 MB/sec	High	Standard
HBA Element 133	100-200 MB/sec	Continuous	Low

Element Configuration Attribute Table

FIG. 12

12/13

800

Select Host and Configuration Policy

Select Policy To Configure 802

Bronze Configuration
Silver Configuration
Gold Configuration
Platinum Configuration

803
New

Select Desired Throughput for Configuration 804

10 100 200 1000 MegaBytes per second

806
Selected Throughput 100 MB/sec

Select Desired Availability Level 808

810a ☐ Standard Availability
(No data or hardware redundancy)

810b ☒ High Availability
Data Redundancy and multiple paths to storage.

810c ☐ Continuous Availability
(High data and hardware redundancy, no single point of failure)

Select Desired Latency Level 812

814a ☐ Low Latency

814b ☒ Standard Latency

814c ☐ High Latency

820

FIG. 13

13/13




FIG. 14